

LED Warning Lights



LED Vision Warning Bar



LED Vision KL Series



LED Vision KS Series



LED Vision Covert



LED Vision KL Series



5 YR WARRANTY

Found in
Emergency
Lighting 2009
catalogue
- pg 47.

- Dimming function for controllable light output.
- No external flasher required. Up to 25 flash patterns available.
- Dual voltage 12v to 24v operation.
- Epoxy encapsulated electronics for environmental & vibration protection.
- Linear lens with 6 high output LEDs.
- LEDs rated to 100,000 hours of operation.
- Wide angle viewing linear lens.
- Unit can be synchronised with other K Series LEDs.

Part Numbers:

KLLED06B-A

KLLED06B-B

KLLED06B-R

KLLED06B-W

LED Vision KS Series



5 YR WARRANTY

Found in
Emergency
Lighting 2009
catalogue
- pg 46.

- Dimming function for controllable light output.
- No external flasher required. Up to 25 flash patterns available.
- Dual voltage 12v to 24v operation.
- Epoxy encapsulated electronics for environmental & vibration protection.
- Split flash patterns.
- LEDs rated to 100,000 hours of operation.
- Wide angle viewing lens.
- Unit can be synchronised with other K Series LEDs.

Part Numbers:

KSLED04B-AA

KSLED04B-BB

KSLED04B-RR

KSLED04B-WW

LED Vision Warning Bar



5 YR WARRANTY

Found in
Emergency
Lighting 2009
catalogue
- pg 48-49.

- Dimming function for controllable light output.
- No external flasher required. Up to 26 flash patterns available.
- Dual voltage 12v to 24v operation.
- LEDs rated to 100,000 hours of operation.
- Wide angle viewing linear lens.
- Adjustable mounting brackets as standard.
- Virtually unlimited colour combinations available. *on request
- Epoxy encapsulated electronics for environmental & vibration protection.

Part Numbers:

LSWLS-3 X A

LSWLS-3 X B

LSWLS-3 X G

LSWLS-3 X R

LSWLS-3 X RB

LSWLS-3 X W

Replace X with the amount
of LED modules required
(2, 4, 6, 8 or 10)

LED Vision Covert



5 YR WARRANTY

Found in
Emergency
Lighting 2009
catalogue
- pg 50.

- Dimming function for controllable light output.
- No external flasher required. Up to 30 flash patterns available.
- Dual voltage 12v to 24v operation.
- LEDs rated to 100,000 hours of operation.
- Real time flash pattern indicator on rear of unit.
- User controls on rear of unit - Flash Select, Dimming, Reset.
- Permanent bolt down mounting option.
- Suction cups for quick and easy windscreen mounting.
- 2900mm lead to standard cigar/DIN plug.

Part Numbers:

LSDL-42TEAA

LSDL-42TERB

03/02/10