

N25 LEDX Worklamp



Part No. 981-013



***+ 30%
output***



N25 LEDX Worklamp



**+ 30%
output**

- Advanced electronics & lens design boosts light output by 30% over the standard N25 LED range without increasing current draw.
- Latest heavy duty LED technology with a life-span of up to 50,000 hours.
- 6000 K colour temperature, whiter than daylight, for reduced eye strain and increased safety.
- Extreme shock resistance - 60G.
- Ultra low current draw - 0.7A @ 24V.
- Deutsch DT series 2 pin connector encapsulated in lamp body.
- Over voltage, over temp, spike & polarity protected.
- Heavy duty anti-vibration mounting system.
- Environmentally sealed compact cast alloy body - IP68.
- 12-80V operation.

Wide Flood:

981-013

Similar products also available:

N25 LED Worklamp



- Heavy duty LED technology with a life-span of up to 50,000 hours.
- 6000 K colour temperature, whiter than daylight, for reduced eye strain and increased safety.
- Extreme shock resistance - 60G.
- Ultra low current draw - 0.7A @ 24V.
- Deutsch DT series 2 pin connector on fly lead.
- Over voltage, over temp, spike & polarity protected.
- Heavy duty anti-vibration mounting system.
- Environmentally sealed compact cast alloy body - IP68.
- 10-80V operation.

Flood:

981-001

Wide Flood

981-006

N220 LED Worklamp



- Latest LED technology with a life-span of up to 50,000 hours.
- 5500 K colour temperature, equal to daylight, for reduced eye strain and increased safety.
- Extreme shock resistance - 60G.
- Low current draw 2.2A @ 24V.
- Deutsch DT series 2 pin connector encapsulated in lamp body.
- Over voltage, over temp, spike & polarity protected.
- Latest heavy duty LED technology.
- Heavy duty anti-vibration mounting system.
- All components sealed within cast alloy body - IP68.

Wide Flood:

982-001

N25 Reverse Lamp



- ADR compliant vehicle reverse lamp.
- Environmentally sealed compact body - IP67.
- 1000 hour heavy duty bulb pre-fitted.
- Heavy Duty anti-vibration mounting system.
- AMP connector moulded into body. Cover boot supplied.
- Rotate lens for pendant, left hand or right hand side mount.
- Free-Form optics for superior light dispersion.
- Available in 12V & 24V operation.

12V:

925-154

24V

925-135

18/08/10